

NUDURA 'EZ' BUCK w/  
DIMENSIONAL LUMBER AS SHOWN

ALTERNATIVE BUCK METHODS  
APPLIED:

WOOD, VINYL, STEEL, ETC. BUCK  
MATERIAL FASTENED TO  
CONCRETE w/ EMBEDDED SPIRAL  
NAILS, BOLTS, SCREWS IN  
STAGGERED PATTERN, OR AS PER  
MANUFACTURERS SPECIFICATION

1/2" (13mm) GYPSUM  
BOARD

NUDURA 12" (305mm)  
STANDARD FORM UNIT

HORIZ/VERT  
REINFORCEMENT AS PER  
CODE OR AS SPECIFIED

BRICK VENEER c/w 1"  
(25mm) AIR SPACE AND  
BRICK TIES

OPENING REINFORCEMENT AS  
PER CODE OR AS SPECIFIED

BRICK RETURN TO COVER AIR  
SPACE

VAPOR BARRIER  
SEALED TO FRAME

GYPSUM BOARD  
RETURN TO FRAME

NUDURA WATERPROOF  
MEMBRANE LAPPING VAPOUR  
BARRIER TO COMPLETE AIR  
SEAL

FRAME ANCHOR CLIPS  
SECURED TO BUCK  
AND FRAME AS  
SPECIFIED

ALUMINUM WINDOW  
FRAME

CONTINUOUS CAULKING  
AROUND FRAME AT CONTACT  
TO MASONRY

1 1/2" (38mm)  
MIN. COVER

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER

THIS DETAIL IS SUITABLE FOR NON-COMBUSTIBLE 1 TO 3 STOREY HIGH APPLICATIONS AS  
PERMITTED UNDER LOCAL CODES; FOR WINDOWS IN BRICK CLAD MULTI-STOREY  
APPLICATIONS, REFER TO DETAIL E12D06 UNDER THIS SECTION



**NUDURA**

**INTEGRATED BUILDING TECHNOLOGY**

*Building Value.*

NUDURA 12" (305mm) FORM UNIT  
WINDOW JAMB DETAIL  
BRICK VENEER FINISH  
ALUMINUM FRAMED WINDOW  
WOOD ROUGH BUCK

REV. NO.  
003 KS  
REV. DATE:  
MAY 2010  
DATE:  
T. VAN CLIEAF

DWG NO.  
E12D04  
SCALE:  
1 : 8