

NUDURA STANDARD 8" (203mm) FORM UNIT

BRICK VENEER c/w 1" (25mm) AIR SPACE AND BRICK TIES

HORIZ/VERT REINFORCEMENT AS PER CODE OR AS SPECIFIED

THROUGH WALL FLASHING AS PER CODE OR AS SPECIFIED

$\frac{3}{16}$ " (5mm) ACRYLIC PARGE COAT

NUDURA 8" (203mm) BRICK LEDGE FORM UNIT

$\frac{1}{2}$ " (13mm) GYPSUM BOARD

WET SET DOWELS TO MATCH VERTICAL REINFORCEMENT BETWEEN POURS OR AS SPECIFIED

GRANULAR FILL
CONCRETE SLAB

NUDURA FLOOR TECHNOLOGY

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 8" (203mm) FORM UNIT
STEM WALL AT SLAB ON GRADE
BRICK VENEER FINISH
INSULATED

REV. NO.
003 KS

REV. DATE:
FEB 2010

DRAWN BY:
T. VAN CLIEAF

DWG NO.

B8C11

SCALE:
1 : 8