

NUDURA 8" (203mm)  
STANDARD FORM UNIT

BRICK VENEER c/w  
1"(25mm) AIR SPACE  
AND BRICK TIES

WET SET DOWELS  
TO MATCH VERTICAL  
REINFORCEMENT  
BETWEEN POUR OR  
AS SPECIFIED

THROUGH WALL  
FLASHING AND  
WEEP HOLES AS  
PER CODE OR AS  
SPECIFIED

FINISHED GRADE  
MINIMUM 6"  
(152mm) OR AS  
PER CODE (SEE  
NOTE)

$\frac{3}{16}$ " (5mm) ACRYLIC  
PARGE COAT WHERE  
EXTENDED ABOVE  
GRADE

NUDURA  
WATERPROOFING MEMBRANE

$\frac{1}{2}$ " (13mm)  
GYPSUM BOARD

HORIZ/VERT  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

SUB FLOOR

FLOOR  
JOISTS/TRUSSES  
AS SPECIFIED

PROPRIETARY  
EMBEDDED JOIST  
ANCHORAGE SYSTEM  
OR EQUIVALENT

NUDURA 8"  
(203mm) BRICK  
LEDGE FORM UNIT

$\frac{1}{2}$ " (13mm)  
GYPSUM BOARD

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER

NOTE: FINISHED GRADE LEVEL SPECIFIED FOR  
FROST PRONE AREAS. FOR ALTERNATIVE GRADE  
LEVEL SEE DETAIL C6A30



**NUDURA**

**INTEGRATED BUILDING TECHNOLOGY**

*Building Value.*

NUDURA 8" (203mm) FORM UNIT  
MULTI-PURPOSE HANGER  
BRICK VENEER FINISH

REV. NO.  
004 KS  
REV. DATE:  
AUGUST 2010  
DRAWN BY:  
T. VAN CLIEAF

DWG NO.  
C8A12  
SCALE:  
1 : 8