

NUDURA 8" (203mm)  
STANDARD FORM UNIT

ANGLED FIELD CUT  
OVER WIDTH OF  
OPENING TO ALLOW  
FOR CONCRETE HEAD

THROUGH WALL  
FLASHING AS PER  
CODE OR AS  
SPECIFIED

STEEL LINTEL AS  
SPECIFIED (w/ BOLTS  
OR NELSON STUDS  
EMBEDDED AS PER  
OPENING REQUIREMENTS)

CONTINUOUS  
CAULKING AROUND  
FRAME AT CONTACT  
TO MASONRY

ALUMINUM WINDOW  
FRAME

CONTINUOUS  
CAULKING AROUND  
FRAME AT CONTACT  
TO MASONRY

MASONRY OR  
BRICK SILL  
COURSE

SILL PAN (OPTIONAL)

BRICK VENEER c/w 1"  
(25mm) AIR SPACE AND  
BRICK TIES

HORIZ/VERT REINFORCEMENT  
AS PER CODE OR AS  
SPECIFIED

1/2" (13mm) GYPSUM  
BOARD

LINTEL REINFORCEMENT AS  
PER CODE OR AS SPECIFIED

1 1/2"  
(38mm) MIN.  
COVER

VAPOUR BARRIER  
SEALED TO FRAME

NUDURA WATERPROOF  
MEMBRANE LAPPED OVER  
VAPOUR BARRIER TO  
COMPLETE AIR SEAL

GYPSUM BOARD RETURN TO  
FRAME

VAPOUR BARRIER  
SEALED TO FRAME

OPENING REINFORCEMENT AS  
PER CODE OR AS SPECIFIED

1/2" (13mm)  
GYPSUM BOARD

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER



# NUDURA

INTEGRATED BUILDING TECHNOLOGY

*Building Value.*

NUDURA 8" (203mm) FORM UNIT  
WINDOW HEAD/SILL DETAIL  
BRICK VENEER FINISH  
ALUMINUM FRAMED WINDOW  
CONCRETE MOUNTED

REV. NO.  
002 KS  
REV. DATE:  
MAY 2010  
DRAWN BY:  
T. VAN CLIEAF

DWG NO.  
E8D05  
SCALE:  
1 : 8