

FLASHING AS SPECIFIED

WOOD BLOCKING AND PLYWOOD AT 5° SLOPE

NON-COMBUSTIBLE FIBERGLASS BATT INSULATION ON VAPOR BARRIER

NUDURA 10" (254mm) STANDARD FORM UNIT

EPS CANT STRIP

HORIZ/VERT REINFORCEMENT AS PER CODE OR AS SPECIFIED

FIBER BOARD SUBSTRATE w/ ROOF MEMBRANE ON CONCRETE SLAB

ADDITIONAL BRACING REQUIRED DURING ROOF SLAB POUR

WET SET DOWELS FIELD BENT INTO SLAB AS SPECIFIED

NUDURA 10" (254mm) HEIGHT ADJUSTER TIE

WET SET DOWEL TO MATCH VERTICAL REINFORCEMENT BETWEEN POUR OR AS SPECIFIED

THERMAL BARRIER & INSULATED CONCRETE ROOF FORM INSTALLED AS PER MANUFACTURERS SPECIFICATIONS

BRICK VENEER c/w 1" (25mm) AIR SPACE AND BRICK TIES

1/2" (13mm) GYPSUM BOARD

DISCLAIMER NOTICE:  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER



# NUDURA

INTEGRATED BUILDING TECHNOLOGY

*Building Value.*

NUDURA 10" (254mm) FORM UNIT  
ICRS CONNECTION  
ICRS RESTING ON FORM  
EXTERIOR SIDE WALL  
BRICK VENEER FINISH

REV. NO.  
003 KS  
DATE:  
APRIL 2010  
DRAWN BY:  
T. VAN CLIEAF

DWG NO.  
F10D03  
SCALE:  
1 : 8