

FLASHING AS SPECIFIED

WOOD BLOCKING AND PLYWOOD AT 5° SLOPE

NON-COMBUSTIBLE FIBERGLASS BATT INSULATION ON VAPOR BARRIER

EPS CANT STRIP

BRICK VENEER c/w 1" (25mm) AIR SPACE AND BRICK TIES

FIBER BOARD SUBSTRATE w/ ROOF MEMBRANE ON 3 1/2" (89mm) RIGID INSULATION

V-CLIP WALL PANEL ANCHOR

FORM PANELS c/w INSERT WEBS-CUT TO SUIT ROOF CONNECTION-ADDITIONAL FORM SUPPORT AS REQUIRED

MASONITE BEARING PAD

WET SET DOWELS TO MATCH VERTICAL REINFORCEMENT BETWEEN POUR OR AS SPECIFIED

HORIZ/VERT REINFORCEMENT AS PER CODE OR AS SPECIFIED

HOLLOW CORE PRECAST SLAB

FINISH AS SPECIFIED

DOWELS FIELD BENT AND GROUTED INTO SHEAR KEY JOINT b/n PANELS AS SPECIFIED

1/2" (13mm) GYPSUM BOARD

NUDURA 10" (254mm) STANDARD FORM UNIT

DISCLAIMER NOTICE:
 SPECIFIC INFORMATION
 REQUIRED FOR COMPLIANCE
 WITH LOCAL CODES IS THE
 RESPONSIBILITY OF THE
 DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 10" (254mm) FORM UNIT
 HOLLOW CORE PRECAST ROOF
 EXTERIOR BEARING WALL DETAIL
 BRICK VENEER FINISH

REV. NO.
003 KS
 REV. DATE:
APRIL 2010
 DRAWN BY:
T. VAN CLIEAF

DWG NO.
F10E02
 SCALE:
1 : 8