



WINDOW FRAMING  
BY OTHERS

FOR MULTI-STOREY  
APPLICATIONS, EIFS  
LAMINA TO LAP  
BACK AROUND  
BUCK TO LINK w/  
CONCRETE

GYPSUM BOARD RETURN  
TO FRAME

FOAM BACKER ROD  
AND CONTINUOUS  
CAULKING AROUND  
FRAME

VAPOR BARRIER SEALED  
TO FRAME AT SILL  
CONDITION

OPENING  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

COMPRESSIBLE AIR SEAL  
GASKET APPLIED TO  
FULL LENGTH REAR  
EDGE OF SILL PRIOR TO  
FRAME INSTALLATION

NUDURA 6" (152mm)  
STANDARD FORM UNIT

HORIZ/VERT  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

DRAINABLE EXTERIOR  
INSULATION  
FINISHING SYSTEM

1/2" (13mm)  
GYPSUM BOARD

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER



NUDURA 6" (152mm) FORM UNIT  
WINDOW SILL DETAIL  
DRAINABLE EIFS  
ALUMINUM FRAMED WINDOW  
CONCRETE MOUNTED

REV. NO. 000	DWG NO. H6E07
REV. DATE: JUNE 2010	
DRAWN BY: K. STILL	SCALE: 1 : 4