

NUDURA 8" (203mm)
STANDARD FORM UNIT

DECORATIVE EPS FOAM
TRIM (HEAD AND SILL)
APPLIED TO NUDURA
FORM USING EPS
COMPATIBLE
ADHESIVE

FASTEN STUCCO MESH TO
BACK OF TEMPORARY BUCK
TO ALLOW MESH TO BOND
WITH CONCRETE

ALUMINUM WINDOW
FRAME BY OTHERS

FOR MULTI-STOREY
APPLICATIONS, EIFS
LAMINA TO LAP BACK
AROUND BUCK TO
LINK w/ CONCRETE

FOAM BACKER ROD
AND CONTINUOUS
CAULKING AROUND
FRAME

OPENING
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

DIRECT APPLIED
ACRYLIC FINISH

1/2" (13mm) GYPSUM
BOARD

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

LINTEL
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

1 1/2"
(38mm) MIN.
COVER

VAPOR BARRIER c/w
FOAM ROD/CAULK OR
SEAL TO INTERIOR
EDGE OF FRAME

GYPSUM BOARD
RETURN TO FRAME

VAPOR BARRIER SEALED
TO FRAME AT SILL
CONDITION

COMPRESSIBLE AIR
SEAL GASKET APPLIED
TO FULL LENGTH REAR
EDGE OF SILL PRIOR
TO FRAME INSTALLATION

1/2" (13mm) GYPSUM
BOARD

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 8" (203mm) FORM UNIT
WINDOW HEAD/SILL DETAIL
EXTERIOR FINISH AS SPECIFIED
ALUMINUM FRAMED WINDOW
CONCRETE MOUNTED

REV. NO.
001 KS

REV. DATE:
SEPT 2010

DRAWN BY:
T. VAN CLIEAF

DWG NO.
E8D07

SCALE:
1 : 8