

FASTEN STUCCO MESH  
TO BUCK PRIOR TO  
PLACING BUCK AT  
JAMB CONDITION

1/2" (13mm)  
GYPSUM BOARD

NUDURA 6"  
(152mm)  
STANDARD FORM  
UNIT

HORIZ/VERT  
REINFORCEMENT  
AS PER CODE OR  
AS SPECIFIED

DIRECT APPLIED  
ACRYLIC FINISH

OPENING  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

DECORATIVE EPS  
FOAM TRIM APPLIED  
TO NUDURA FORM  
USING ADHESIVE

GYPSUM BOARD  
RETURN TO FRAME

ALUMINUM JAMB  
ANCHOR CLIPS

VAPOR BARRIER  
SEALED TO  
INTERIOR EDGE OF  
FRAME

WINDOW FRAME  
BY OTHERS

1 1/2"  
(38mm) MIN.  
COVER

FOAM BACKER ROD AND  
CONTINUOUS CAULKING  
AROUND WINDOW FRAME  
c/w DRAIN SLOT AT  
CENTER OF SILL

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER



**NUDURA**

**INTEGRATED BUILDING TECHNOLOGY**

*Building Value.*

NUDURA 6" (152mm) FORM UNIT  
WINDOW JAMB DETAIL  
EXTERIOR FINISH AS SPECIFIED  
ALUMINUM FRAMED WINDOW  
CONCRETE MOUNTED

REV. NO.  
000

REV. DATE:  
JUNE 2010

DRAWN BY:  
K. STILL

DWG NO.

H6D06

SCALE:

1 : 4