

OPENING REINFORCEMENT
AS PER CODE OR AS
SPECIFIED

NUDURA 12" (305mm)
STANDARD FORM UNIT

1/2" (13mm)
GYPSUM BOARD

HORIZ/VERT
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

DIRECT APPLIED
ACRYLIC FINISH

FASTEN STUCCO MESH TO
BUCK PRIOR TO PLACING
BUCK AT JAMB CONDITION

DECORATIVE EPS FOAM TRIM
APPLIED TO NUDURA FORM
USING ADHESIVE

WOOD,VINYL,STEEL,ETC. BUCK MATERIAL
FASTENED TO CONCRETE w/EMBEDDED
SPIRAL NAILS,BOLTS,SCREWS IN
STAGGERED PATTERN, OR AS PER
MANUFACTURERS SPECIFICATION

GYPSUM BOARD
RETURN TO FRAME

VAPOR BARRIER
SEALED TO
INTERIOR EDGE OF
FRAME

ALUMINUM JAMB
ANCHOR CLIPS

WINDOW FRAME BY
OTHERS

FOAM BACKER ROD AND
CONTINUOUS CAULKING
AROUND WINDOW FRAME
c/w DRAIN SLOT AT
CENTER OF SILL

1 1/2"
(38mm)MIN.
COVER

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 12" (305mm) FORM UNIT
WINDOW JAMB DETAIL
EXTERIOR FINISH AS SPECIFIED
ALUMINUM FRAMED WINDOW
WOOD ROUGH BUCK

REV. NO.
003 KS

REV. DATE:
MAY 2010

DRAWN BY:
T. VAN CLIEAF

DWG NO.

E12D02

SCALE:

1 : 8