

FASTEN STUCCO MESH
TO BACK OF
TEMPORARY BUCK TO
ALLOW MESH TO
BOND WITH CONCRETE

1/2" (13mm)
GYPSUM BOARD

NUDURA 6"
(152mm)
STANDARD FORM
UNIT

HORIZ/VERT
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

DIRECT APPLIED
ACRYLIC FINISH

OPENING
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

GYPSUM BOARD
RETURN TO FRAME

ALUMINUM JAMB
ANCHOR CLIPS

VAPOR BARRIER
SEALED TO
INTERIOR EDGE OF
FRAME

WINDOW FRAME
BY OTHERS

FOAM BACKER ROD AND
CONTINUOUS CAULKING
AROUND WINDOW FRAME
c/w DRAIN SLOT AT
CENTER OF SILL

1 1/2"
(38mm) MIN.
COVER

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 6" (152mm) FORM UNIT
WINDOW JAMB DETAIL
DIRECT APPLIED ACRYLIC FINISH
ALUMINUM FRAMED WINDOW
CONCRETE MOUNTED

REV. NO.
000

REV. DATE:
JUNE 2010

DRAWN BY:
K. STILL

DWG NO.

H6C06

SCALE:

1 : 4