

FLASHING AS SPECIFIED

WOOD BLOCKING AND PLYWOOD AT 5° SLOPE

NON-COMBUSTIBLE FIBERGLASS BATT INSULATION ON VAPOR BARRIER

NUDURA 8" (203mm) STANDARD FORM UNIT

EPS CANT STRIP

HORIZ/VERT REINFORCEMENT AS PER CODE OR AS SPECIFIED

FIBER BOARD SUBSTRATE w/ ROOF MEMBRANE ON CONCRETE SLAB

ADDITIONAL BRACING REQUIRED DURING ROOF SLAB POUR

WET SET DOWELS FIELD BENT INTO SLAB AS SPECIFIED

NUDURA 8" (203mm) HEIGHT ADJUSTER TIE

WET SET DOWEL TO MATCH VERTICAL REINFORCEMENT BETWEEN POUR OR AS SPECIFIED

THERMAL BARRIER & INSULATED CONCRETE ROOF FORM INSTALLED AS PER MANUFACTURERS SPECIFICATIONS

EXTERIOR FINISH AS SPECIFIED

1/2" (13mm) GYPSUM BOARD

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 8" (203mm) FORM UNIT
ICRS CONNECTION
ICRS RESTING ON FORM
EXTERIOR SIDE WALL
EXTERIOR FINISH AS SPECIFIED

REV. NO.
003 KS
DATE:
APRIL 2010
DRAWN BY:
T. VAN CLIEAF

DWG NO.
F8D01
SCALE:
1 : 8