

NUDURA 6" (152mm)
STANDARD FORM UNIT

BRICK VENEER c/w 1"
(25mm) AIR SPACE AND
BRICK TIES

THROUGH WALL
FLASHING AS PER
CODE OR AS
SPECIFIED

STEEL LINTEL

CONTINUOUS
CAULKING AROUND
FRAME AT CONTACT
TO MASONRY

ALUMINUM WINDOW
FRAME

CONTINUOUS
CAULKING AROUND
FRAME AT CONTACT
TO MASONRY

MASONRY OR
BRICK SILL
COURSE

SILL PAN
(OPTIONAL)

2x2" (38x38mm)
ROUGH NAILER

HORIZ/VERT REINFORCEMENT
AS PER CODE OR AS
SPECIFIED

1/2" (13mm) GYPSUM
BOARD

LINTEL REINFORCEMENT AS
PER CODE OR AS SPECIFIED

1 1/2"
(38mm) MIN.
COVER

VAPOUR BARRIER
SEALED TO FRAME

WOOD, VINYL, STEEL, ETC. BUCK
MATERIAL FASTENED TO
CONCRETE w/ EMBEDDED SPIRAL
NAILS, BOLTS, SCREWS IN
STAGGERED PATTERN, OR AS
PER MANUFACTURERS
SPECIFICATION

NUDURA WATERPROOF
MEMBRANE LAPPED OVER
VAPOUR BARRIER TO
COMPLETE AIR SEAL

GYPSUM BOARD RETURN TO
FRAME

2x3" (38x64mm) ROUGH
NAILER

VAPOUR BARRIER
SEALED TO FRAME

OPENING REINFORCEMENT AS
PER CODE OR AS SPECIFIED

1/2" (13mm)
GYPSUM BOARD

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER

THIS DETAIL IS SUITABLE FOR NON-COMBUSTIBLE 1 TO 3 STOREY HIGH APPLICATIONS AS PERMITTED UNDER LOCAL CODES; FOR WINDOWS IN BRICK CLAD MULTI-STOREY APPLICATIONS, REFER TO DETAIL E6D03 UNDER THIS SECTION



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 6" (152mm) FORM UNIT
WINDOW HEAD/SILL DETAIL
BRICK VENEER FINISH
ALUMINUM FRAMED WINDOW
WOOD ROUGH BUCK

REV. NO.
006 KS

DATE:
MAY 2010

DRAWN BY:
J. NEILON

DWG NO.

E6D01

SCALE:
1 : 8