

NUDURA 12"
(305mm) STANDARD
FORM UNIT

BRICK VENEER c/w
1" (25mm) AIR
SPACE AND BRICK
TIES

WET SET DOWELS
TO MATCH VERTICAL
REINFORCEMENT
BETWEEN POUR OR
AS SPECIFIED

HORIZ/VERT
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

THROUGH WALL
FLASHING AND
WEEP HOLES AS
PER CODE OR AS
SPECIFIED

FINISHED GRADE
MINIMUM 6"
(152mm) OR AS
PER CODE (SEE
NOTE)

$\frac{3}{16}$ " (5mm) ACRYLIC
PARGE COAT WHERE
EXTENDED ABOVE
GRADE

NUDURA
WATERPROOFING MEMBRANE

4 1/2" [114mm]

2" (51mm) MIN.

EQUAL TO RIM JOIST MINIMUM 7 1/2" (191mm)

1/2" (13mm)
GYPSUM BOARD

SUB FLOOR

FLOOR
JOISTS/TRUSSES
AS SPECIFIED

2 1/2" (64mm) MIN.

DOUBLE BOLT
SHOWN OR
STAGGERED ANCHOR
BOLTS AS
SPECIFIED

CUT EPS FOAM AT
BOLT LOCATIONS
ONLY

1/2" (13mm)
GYPSUM BOARD

NUDURA 12" (305mm)
BRICK LEDGE FORM
UNIT

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER

NOTE: FINISHED GRADE LEVEL SPECIFIED FOR
FROST PRONE AREAS. FOR ALTERNATIVE GRADE
LEVEL SEE DETAIL C6A33



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 12" (305mm) FORM UNIT
MULTI-PURPOSE HANGER
BRICK VENEER FINISH

REV. NO.
004 KS
REV. DATE:
AUGUST 2010
DRAWN BY:
T. VAN CLIEAF

DWG NO.
C12A07
SCALE:
1 : 8