



EXTERIOR FINISH
AS SPECIFIED

HORIZ/VERT
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

WET SET DOWELS
TO MATCH VERTICAL
REINFORCEMENT
BETWEEN POUR OR
AS SPECIFIED

FINISHED GRADE
MINIMUM 6"
(152mm) OR AS
PER CODE

$\frac{3}{16}$ " (5mm)
ACRYLIC PARGE
COAT

NUDURA WATERPROOF
MEMBRANE

$\frac{1}{2}$ " (13mm)
GYPSUM BOARD

BLOCKING BETWEEN
JOISTS

JOISTS/TRUSSES
AS SPECIFIED

$\frac{1}{2}$ " (13mm)
GYPSUM BOARD

PROPRIETARY EMBEDDED
JOIST ANCHORAGE
SYSTEM OR EQUIVALENT

NUDURA 6" (152mm)
STANDARD FORM UNIT

$\frac{1}{2}$ " (13mm)
GYPSUM BOARD

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA 6" (152mm) FORM UNIT
PROPRIETARY EMBEDDED JOIST
ANCHORAGE SYSTEM
EXTERIOR FINISH AS SPECIFIED

REV. NO. 004 KS	DWG NO. C6A11
REV. DATE: AUGUST 2010	
DRAWN BY: J. NEILON	SCALE: 1 : 8