



FORM PANELS c/w INSERT WEBS—CUT TO SUIT FLOOR CONNECTION— ADDITIONAL FORM SUPPORT AS REQUIRED

WET SET DOWELS FIELD BENT INTO SLAB AS SPECIFIED

U BRACKET ANCHOR INSERT

EXTERIOR FINISH AS SPECIFIED

WET SET DOWELS TO MATCH VERTICAL REINFORCEMENT BETWEEN POUR OR AS SPECIFIED

HORIZ/VERT REINFORCEMENT AS PER CODE OR AS SPECIFIED

GYPSUM BOARD FINISHED/FIRE STOP INSTALLED AT JOISTS AS PER CODE

COMPOSITE STEEL DECK—SLAB AND REINFORCEMENT AS SPECIFIED

OVSJ

INTERIOR INSULATION REMOVED AT JOIST LOCATIONS

1/2" (13mm) GYPSUM BOARD

NUDURA 12" (305mm) STANDARD FORM UNIT

**DISCLAIMER NOTICE:**  
 SPECIFIC INFORMATION  
 REQUIRED FOR COMPLIANCE  
 WITH LOCAL CODES IS THE  
 RESPONSIBILITY OF THE  
 DESIGNER



NUDURA 12" (305mm) FORM UNIT  
 COMPOSITE STEEL DECK—SLAB  
 STEEL JOIST ON EXT. BEARING WALL  
 INTERMEDIATE FLOOR CONNECTION  
 EXTERIOR FINISH AS SPECIFIED

REV. NO. 004 KS	DWG NO. D12C06
DATE: MARCH 2010	
DRAWN BY: T. VAN CLIEAF	SCALE: 1 : 8