

NUDURA 6" (152mm)
STANDARD FORM UNIT

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

ADDITIONAL BRACING
REQUIRED DURING
FLOOR SLAB POUR

BRICK VENEER c/w 1"
(25mm) AIR SPACE
AND BRICK TIES

WET SET DOWELS
FIELD BENT INTO SLAB
AS SPECIFIED

THROUGH WALL FLASHING
AS PER CODE OR AS
SPECIFIED

NUDURA 6" (152mm)
BRICK LEDGE FORM
UNIT

$\frac{3}{16}$ " (5mm) ACRYLIC
PARGE COAT

NUDURA WATERPROOF
MEMBRANE

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

CONCRETE SLAB

INSULATED CONCRETE FLOOR
FORM INSTALLED AS PER
MANUFACTURERS
SPECIFICATIONS

THERMAL BARRIER AS PER
FLOOR MANUFACTURERS
SPECIFICATION

TEMPORARY STEEL
ANGLE

NUDURA 6" (152mm)
HEIGHT ADJUSTER TIE

WET SET DOWELS TO
MATCH VERTICAL
REINFORCEMENT BETWEEN
POURS OR AS SPECIFIED

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 6" (152mm) FORM UNIT
ICFS CONNECTION
ICFS RESTING ON FORM
EXTERIOR BEARING WALL AT GRADE
BRICK VENEER FINISH

REV. NO.
005 KS

REV. DATE:
APRIL 2010

DRAWN BY:
T. VAN CLIEAF

DWG NO.
D6D10

SCALE:
1 : 8