

NUDURA 8" (203mm)  
STANDARD FORM UNIT

EXTERIOR FINISH AS  
SPECIFIED

HORIZ/VERT  
REINFORCEMENT AS PER  
CODE OR AS SPECIFIED

FORM PANELS c/w  
INSERT WEBS-CUT TO  
SUIT FLOOR  
CONNECTION-ADDITIONAL  
FORM SUPPORT AS  
REQUIRED

WET SET FIELD DOWELS  
FIELD BENT INTO SLAB  
AS SPECIFIED

$\frac{3}{16}$ " (5mm)  
ACRYLIC PARGE COAT

NUDURA WATERPROOF  
MEMBRANE

WET SET DOWELS TO  
MATCH VERTICAL  
REINFORCEMENT  
BETWEEN POURS OR AS  
SPECIFIED

$\frac{1}{2}$ " (13mm) GYPSUM  
BOARD

STEEL DECK SUPPORT  
WELDING ANCHOR  
INSERT

COMPOSITE STEEL  
DECK-SLAB AND  
REINFORCEMENT AS  
SPECIFIED

INTERIOR INSULATION  
TO BE DISCONTINUOUS  
AT FLOOR LINES

OWSJ

MINIMUM  $\frac{1}{32}$ " (0.8mm) x 2  
 $\frac{1}{2}$ " (63.5mm) GALVANIZED  
STEEL CHANNEL CAP  
TO PROVIDE THERMAL BARRIER  
PROTECTION

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER



**NUDURA**

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 8" (203mm) FORM UNIT  
COMPOSITE STEEL DECK-SLAB  
STEEL JOISTS ON SIDE WALL  
EXTERIOR FINISH AS SPECIFIED

REV. NO.  
004 KS  
REV. DATE:  
MARCH 2010  
DRAWN BY:  
T. VAN CLIEAF

DWG NO.  
D8C04  
SCALE:  
1 : 8