

NUDURA 8" (203mm)
STANDARD FORM UNIT

BRICK VENEER c/w
1" (25mm) AIR
SPACE AND BRICK
TIES

FORM PANELS c/w
INSERT WEBS-CUT
TO SUIT FLOOR
CONNECTION-ADDITIONAL
FORM SUPPORT AS
REQUIRED

WET SET FIELD
DOWELS FIELD BENT
INTO SLAB AS
SPECIFIED

THROUGH WALL
FLASHING AS PER
CODE OR AS
SPECIFIED

NUDURA 8" (203mm)
PRE-ASSEMBLED
BRICK LEDGE FORM
UNIT

$\frac{3}{16}$ " (5mm) ACRYLIC
PARGE COAT

NUDURA WATERPROOF
MEMBRANE

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

STEEL DECK SUPPORT
WELDING ANCHOR
INSERT

COMPOSITE STEEL
DECK-SLAB AND
REINFORCEMENT AS
SPECIFIED

INTERIOR INSULATION
TO BE DISCONTINUOUS
AT FLOOR LINES

OWSJ

MINIMUM $\frac{1}{32}$ " (0.8mm) x 2
 $\frac{1}{2}$ " (63.5mm) GALVANIZED
STEEL CHANNEL CAP TO
PROVIDE THERMAL BARRIER
PROTECTION

WET SET DOWELS TO
MATCH VERTICAL
REINFORCEMENT
BETWEEN POURS OR
AS SPECIFIED

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 8" (203mm) FORM UNIT
COMPOSITE STEEL DECK-SLAB
STEEL JOISTS ON SIDE WALL
BRICK VENEER FINISH

REV. NO.
004 KS
REV. DATE:
MARCH 2010
DRAWN BY:
T. VAN CLIEAF

DWG NO.
D8C07
SCALE:
1 : 8