

NUDURA 10" (254mm)
STANDARD FORM UNIT

ANGLED FIELD CUT
OVER WIDTH OF
OPENING TO ALLOW
FOR CONCRETE HEAD

THROUGH WALL
FLASHING AS PER
CODE OR AS
SPECIFIED

STEEL LINTEL AS
SPECIFIED (w/ BOLTS
OR NELSON STUDS
EMBEDDED AS PER
OPENING REQUIREMENTS)

CONTINUOUS
CAULKING AROUND
FRAME AT CONTACT
TO MASONRY

ALUMINUM WINDOW
FRAME

CONTINUOUS
CAULKING AROUND
FRAME AT CONTACT
TO MASONRY

MASONRY OR
BRICK SILL
COURSE

SILL PAN (OPTIONAL)

BRICK VENEER c/w 1"
(25mm) AIR SPACE AND
BRICK TIES

HORIZ/VERT REINFORCEMENT
AS PER CODE OR AS
SPECIFIED

1/2" (13mm) GYPSUM
BOARD

LINTEL REINFORCEMENT AS
PER CODE OR AS SPECIFIED

1 1/2"
(38mm) MIN.
COVER

VAPOUR BARRIER
SEALED TO FRAME

NUDURA WATERPROOF
MEMBRANE LAPPED OVER
VAPOUR BARRIER TO
COMPLETE AIR SEAL

GYPSUM BOARD RETURN TO
FRAME

VAPOUR BARRIER
SEALED TO FRAME

OPENING REINFORCEMENT AS
PER CODE OR AS SPECIFIED

1/2" (13mm)
GYPSUM BOARD

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 10" (254mm) FORM UNIT
WINDOW HEAD/SILL DETAIL
BRICK VENEER FINISH
ALUMINUM FRAMED WINDOW
CONCRETE MOUNTED

REV. NO.
002 KS
REV. DATE:
MAY 2010
DRAWN BY:
T. VAN CLIEAF

DWG NO.
E10D05
SCALE:
1 : 8