

OPENING REINFORCEMENT
AS PER CODE OR AS
SPECIFIED

NUDURA 10" (254mm)
STANDARD FORM UNIT

1/2" (13mm)
GYPSUM BOARD

HORIZ/VERT
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

DIRECT APPLIED
ACRYLIC FINISH

FASTEN STUCCO MESH TO
BACK OF TEMPORARY BUCK
TO ALLOW MESH TO BOND
WITH CONCRETE

DECORATIVE EPS FOAM TRIM
APPLIED TO NUDURA FORM
USING ADHESIVE

VAPOR BARRIER
SEALED TO INTERIOR
EDGE OF FRAME

GYPSUM BOARD
RETURN TO FRAME

ALUMINUM JAMB
ANCHOR CLIPS

WINDOW FRAME BY
OTHERS

FOAM BACKER ROD AND
CONTINUOUS CAULKING
AROUND WINDOW FRAME
c/w DRAIN SLOT AT
CENTER OF SILL

1 1/2"
(38mm) MIN.
COVER

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 10" (254mm) FORM UNIT
WINDOW JAMB DETAIL
EXTERIOR FINISH AS SPECIFIED
ALUMINUM FRAMED WINDOW
CONCRETE MOUNTED

REV. NO.
001 KS
REV. DATE:
MAY 2010
DRAWN BY:
T. VAN CLIEAF

DWG NO.
E10D08
SCALE:
1 : 8