

WOOD, VINYL, STEEL, ETC. BUCK MATERIAL FASTENED TO CONCRETE w/ EMBEDDED SPIRAL NAILS, BOLTS, SCREWS IN STAGGERED PATTERN, OR AS PER MANUFACTURERS SPECIFICATIONS

1/2" (13mm) GYPSUM BOARD

VAPOR BARRIER SEALED TO FRAME

GYPSUM BOARD RETURN TO FRAME

OPENING REINFORCEMENT AS PER CODE OR AS SPECIFIED

HORIZ/VERT REINFORCEMENT AS PER CODE OR AS SPECIFIED

ALUMINUM DOOR

CONTINUOUS AIR SEAL CAULKING TO MASONRY

NUDURA 10" (254mm) STANDARD FORM UNIT

BRICK VENEER c/w 1" (25mm) AIR SPACE AND BRICK TIES

DISCLAIMER NOTICE:
 SPECIFIC INFORMATION
 REQUIRED FOR COMPLIANCE
 WITH LOCAL CODES IS THE
 RESPONSIBILITY OF THE
 DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 10" (254mm) FORM UNIT
 WOOD BUCK MOUNTED
 ALUMINUM DOOR JAMB DETAIL
 BRICK VENEER FINISH
 DIRECT ATTACHED

REV. NO.
003 KS

DWG NO.

REV. DATE:
SEPT 2010

E10E02

DRAWN BY:
T. VAN CLIEAF

SCALE:
1 : 8