

NUDURA 10" (254mm)
STANDARD FORM UNIT

BRICK VENEER c/w
1" (25mm) AIR
SPACE AND BRICK
TIES

WEEP HOLES AND
THROUGH WALL
FLASHING AS PER
CODE OR AS
SPECIFIED

STEEL LINTEL
w/CONTINUOUS
CAULKING AROUND
FRAME TO MASONRY

BRICK VENEER
BEYOND

ALUMINUM
COMMERCIAL
THRESHOLD AND
ENTRANCE DOOR

EXTERIOR
CONCRETE
SLAB

NUDURA 10"
(254mm) BRICK
LEDGE FORM
UNIT BEYOND

NUDURA FORM
PANELS c/w INSERT
WEBS-CUT TO SUIT
CONCRETE CAP
PLACEMENT-ADDITIONAL
FORM SUPPORT AS
REQUIRED

1/2" (13mm) GYPSUM
BOARD

HORIZ/VERT
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

LINTEL REINFORCEMENT
AS PER CODE OR AS
SPECIFIED

VAPOR BARRIER
SEALED TO FRAME

WOOD,VINYL,STEEL,ETC.
BUCK MATERIAL FASTENED
TO CONCRETE w/EMBEDDED
SPIRAL NAILS,BOLTS,SCREWS
IN STAGGERED PATTERN,
OR AS PER
MANUFACTURERS
SPECIFICATIONS

FRAME ANCHOR CLIPS
SECURED TO BUCK AND
FRAME AS SPECIFIED

OPENING
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

FLOOR FINISH
AS SPECIFIED

CONCRETE
SLAB ON GRADE

COMPRESSIBLE
FELT FILLER STRIP

EPS FOAM CUT DOWN
THICKNESS OF INTERIOR
SLAB AT EXTENT OF
DOOR OPENING WIDTH

1 1/2"
(38mm) MIN.
COVER

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 10" (254mm) FORM UNIT
WOOD BUCK MOUNTED
ALUMINUM ENTRANCE DOOR
AT HEAD AND CONCRETE THRESHOLD
BRICK VENEER FINISH

REV. NO.
000

REV. DATE:
SEPT 2010

DRAWN BY:
K. STILL

DWG NO.

E10E05

SCALE:

1 : 8