

NUDURA 10" (254mm)
STANDARD FORM UNIT

EXTERIOR FINISH AS
SPECIFIED

STEEL DOOR

THRESHOLD

EXTERIOR
CONCRETE SLAB

COMPRESSIBLE
FELT FILLER
STRIP

NUDURA 10" (254mm)
DOUBLE TAPER TOP
FORM UNIT OR HAND
CUT TAPER AT WIDTH OF
DOOR OPENING (BOTH
SIDES)

1/2" (13mm) GYPSUM
BOARD

LINTEL
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

STEEL DOOR FRAME
c/w CAST IN
ANCHORS

OPENING
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

FLOOR FINISH
AS SPECIFIED

CONCRETE
FLOOR SLAB
ON GRADE

HORIZ/VERT
REINFORCEMENT
AS PER CODE
OR AS SPECIFIED

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 10" (254mm) FORM UNIT
STEEL DOOR AT HEAD/THRESHOLD
EXTERIOR FINISH AS SPECIFIED
DIRECT ATTACHED

REV. NO.
004 KS
REV. DATE:
SEPT 2010
DRAWN BY:
T. VAN CLIEAF

DWG NO.
E10H02
SCALE:
1 : 8