

NUDURA 10" (254mm)
STANDARD FORM UNIT

BRICK VENEER c/w
1" (25mm) AIR
SPACE AND BRICK
TIES

WEEP HOLES AND
THROUGH WALL
FLASHING AS PER
CODE OR AS
SPECIFIED

STEEL LINTEL c/w
CONTINUOUS
CAULKING AT FRAME

BRICK VENEER
BEYOND

1/2" (13mm) GYPSUM
BOARD

LINTEL
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

STEEL DOOR FRAME
c/w CAST IN
ANCHORS

STEEL DOOR

THRESHOLD

OPENING
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

FLOOR FINISH
AS SPECIFIED

COMPRESSIBLE
FELT FILLER
STRIP

CONCRETE
FLOOR SLAB
ON GRADE

NUDURA 10"
(254mm) BRICK
LEDGE FORM UNIT
BEYOND

NUDURA 10"
(254mm) DOUBLE
TAPER TOP FORM
UNIT OR HAND CUT
TAPER AT WIDTH
OF OPENING (BOTH
SIDES)

HORIZ/VERT
REINFORCEMENT
AS PER CODE
OR AS SPECIFIED

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 10" (254mm) FORM UNIT
STEEL DOOR AT HEAD/THRESHOLD
BRICK VENEER FINISH
DIRECT ATTACHED

REV. NO.
004 KS
REV. DATE:
SEPT 2010
DRAWN BY:
T. VAN CLIEAF

DWG NO.
E10H04
SCALE:
1 : 8