

NUDURA 12" (305mm)
STANDARD FORM UNIT

EXTERIOR FINISH AS
SPECIFIED

STEEL DOOR

1/2" (13mm) GYPSUM
BOARD

LINTEL
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

STEEL DOOR FRAME
c/w CAST IN
ANCHORS

THRESHOLD

EXTERIOR
CONCRETE SLAB

COMPRESSIBLE
FELT FILLER
STRIP

NUDURA 12" (305mm)
DOUBLE TAPER TOP
FORM UNIT OR HAND
CUT TAPER AT WIDTH
OF DOOR OPENING
(BOTH SIDES)

OPENING
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

FLOOR FINISH
AS SPECIFIED

CONCRETE
FLOOR SLAB
ON GRADE

HORIZ/VERT
REINFORCEMENT
AS PER CODE
OR AS SPECIFIED

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 12" (305mm) FORM UNIT
STEEL DOOR AT HEAD/THRESHOLD
EXTERIOR FINISH AS SPECIFIED
DIRECT ATTACHED

REV. NO.
004 KS
REV. DATE:
SEPT 2010
DRAWN BY:
T. VAN CLIEAF

DWG NO.
E12H03
SCALE:
1 : 8