

NUDURA 6" (152mm)  
STANDARD FORM UNIT

BRICK VENEER c/w 1"  
(25mm) AIR SPACE AND  
BRICK TIES

THROUGH WALL  
FLASHING AS PER  
CODE OR AS  
SPECIFIED

STEEL LINTEL

CONTINUOUS  
CAULKING AROUND  
FRAME AT CONTACT  
TO MASONRY

ALUMINUM WINDOW  
FRAME

CONTINUOUS  
CAULKING AROUND  
FRAME AT CONTACT  
TO MASONRY

MASONRY OR  
BRICK SILL  
COURSE

SILL PAN  
(OPTIONAL)

2x2" (38x38mm)  
ROUGH NAILER

HORIZ/VERT REINFORCEMENT  
AS PER CODE OR AS  
SPECIFIED

1/2" (13mm) GYPSUM  
BOARD

LINTEL REINFORCEMENT AS  
PER CODE OR AS SPECIFIED

1 1/2"  
(38mm) MIN.  
COVER

VAPOUR BARRIER  
SEALED TO FRAME

WOOD, VINYL, STEEL, ETC. BUCK  
MATERIAL FASTENED TO  
CONCRETE w/ EMBEDDED SPIRAL  
NAILS, BOLTS, SCREWS IN  
STAGGERED PATTERN, OR AS  
PER MANUFACTURERS  
SPECIFICATION

NUDURA WATERPROOF  
MEMBRANE LAPPED OVER  
VAPOUR BARRIER TO  
COMPLETE AIR SEAL

GYPSUM BOARD RETURN TO  
FRAME

2x3" (38x64mm) ROUGH  
NAILER

VAPOUR BARRIER  
SEALED TO FRAME

OPENING REINFORCEMENT AS  
PER CODE OR AS SPECIFIED

1/2" (13mm)  
GYPSUM BOARD

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER

THIS DETAIL IS SUITABLE FOR NON-COMBUSTIBLE 1 TO 3 STOREY HIGH APPLICATIONS AS PERMITTED UNDER LOCAL CODES; FOR WINDOWS IN BRICK CLAD MULTI-STOREY APPLICATIONS, REFER TO DETAIL E6D03 UNDER THIS SECTION



# NUDURA

INTEGRATED BUILDING TECHNOLOGY

*Building Value.*

NUDURA 6" (152mm) FORM UNIT  
WINDOW HEAD/SILL DETAIL  
BRICK VENEER FINISH  
ALUMINUM FRAMED WINDOW  
WOOD ROUGH BUCK

REV. NO.  
006 KS  
DATE:  
MAY 2010  
DRAWN BY:  
J. NEILON

DWG NO.  
E6D01  
SCALE:  
1 : 8