

NUDURA 6" (152mm)  
STANDARD FORM UNIT

1/2" (13mm) GYPSUM  
BOARD

DECORATIVE EPS FOAM  
TRIM (HEAD AND SILL)  
APPLIED TO NUDURA  
FORM USING EPS  
COMPATIBLE  
ADHESIVE

HORIZ/VERT  
REINFORCEMENT AS PER  
CODE OR AS SPECIFIED

FASTEN STUCCO MESH TO  
BACK OF TEMPORARY BUCK  
TO ALLOW MESH TO BOND  
WITH CONCRETE

LINTEL  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

1 1/2"  
(38mm) MIN.  
COVER

ALUMINUM WINDOW  
FRAME BY OTHERS

VAPOR BARRIER c/w  
FOAM ROD/CAULK OR  
SEAL TO INTERIOR  
EDGE OF FRAME

FOR MULTI-STOREY  
APPLICATIONS, EIFS  
LAMINA TO LAP BACK  
AROUND BUCK TO  
LINK w/ CONCRETE

FOAM BACKER ROD  
AND CONTINUOUS  
CAULKING AROUND  
FRAME

GYPSUM BOARD  
RETURN TO FRAME

OPENING  
REINFORCEMENT AS PER  
CODE OR AS SPECIFIED

VAPOR BARRIER SEALED  
TO FRAME AT SILL  
CONDITION

DIRECT APPLIED  
ACRYLIC FINISH

COMPRESSIBLE AIR  
SEAL GASKET APPLIED  
TO FULL LENGTH REAR  
EDGE OF SILL PRIOR  
TO FRAME INSTALLATION

1/2" (13mm) GYPSUM  
BOARD

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER



# NUDURA

INTEGRATED BUILDING TECHNOLOGY

*Building Value.*

NUDURA 6" (152mm) FORM UNIT  
WINDOW HEAD/SILL DETAIL  
DIRECT APPLIED ACRYLIC FINISH  
ALUMINUM FRAMED WINDOW  
CONCRETE MOUNTED

REV. NO.  
000  
REV. DATE:  
SEPT 2010  
DRAWN BY:  
K. STILL

DWG NO.  
E6D12  
SCALE:  
1 : 8