

NUDURA 6" (152mm)
STANDARD FORM UNIT

BRICK VENEER c/w
1" (25mm) AIR
SPACE AND BRICK
TIES

WEEP HOLES AND
THROUGH WALL
FLASHING AS PER
CODE OR AS
SPECIFIED

1 1/2"
(38mm) MIN.
COVER

STEEL LINTEL WITH
CONTINUOUS
CAULKING AROUND
FRAME TO MASONRY

BRICK VENEER
BEYOND

ALUMINUM
COMMERCIAL SIDE
LIGHT FRAME

EXTERIOR
CONCRETE
SLAB

COMPRESSIBLE FELT
FILLER STRIP

NUDURA 6" (152mm)
BRICK LEDGE FORM
UNIT BEYOND

1/2" (13mm)
GYPSUM BOARD

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

LINTEL
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

VAPOR BARRIER
SEALED TO CONCRETE

STEEL LINTEL AS
SPECIFIED (w/NELSON
STUDS OR BOLTS AS
PER OPENING
REQUIREMENTS)

FRAME ANCHOR CLIPS
SECURED TO CONCRETE
AND FRAME AS SPECIFIED

OPENING
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

FLOOR FINISH
AS SPECIFIED

CONCRETE
SLAB ON GRADE

NUDURA 6"
(152mm) DOUBLE
TAPER TOP FORM
UNIT OR HAND CUT
TAPER AT WIDTH
OF DOOR OPENING
(BOTH SIDES)

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 6" (152mm) FORM UNIT
CONCRETE MOUNTED
ALUMINUM TRANSOM AND SIDE LIGHT
AT HEAD AND THRESHOLD
BRICK VENEER FINISH

REV. NO.
005 KS

REV. DATE:
SEPT 2010

DRAWN BY:
T. VAN CLIEAF

DWG NO.
E6E06

SCALE:
1 : 8