

NUDURA 6" (152mm)  
STANDARD FORM UNIT

EXTERIOR FINISH AS  
SPECIFIED

MESH BONDED  
TO EIFS  
LAMINA AT EXTERIOR

FASTEN STUCCO MESH  
TO BUCK PRIOR TO  
PLACING FRAME  
ANCHOR CLIPS

CONTINUOUS AIR SEAL  
CAULKING TO FRAME AND  
EXTERIOR FINISH

ALUMINUM SIDE LIGHT  
FRAME

EXTERIOR CONCRETE  
SLAB

COMPRESSIBLE  
FELT FILLER  
STRIP

NUDURA 6"  
(152mm) DOUBLE  
TAPER TOP FORM  
UNIT OR HAND CUT  
TAPER AT WIDTH OF  
DOOR OPENING  
(BOTH SIDES)

1 1/2"  
(38mm) MIN.  
COVER

1/2" (13mm)  
GYPSUM BOARD

LINTEL  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

VAPOR BARRIER  
SEALED TO CONCRETE

WOOD, VINYL, STEEL, ETC.  
BUCK MATERIAL FASTENED  
TO CONCRETE w/ EMBEDDED  
SPIRAL NAILS, BOLTS, SCREWS  
IN STAGGERED PATTERN,  
OR AS PER  
MANUFACTURERS  
SPECIFICATIONS

FRAME ANCHOR CLIPS  
SECURED TO BUCK AND  
FRAME AS SPECIFIED

OPENING  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

FLOOR FINISH  
AS SPECIFIED

CONCRETE  
SLAB ON GRADE

HORIZ/VERT  
REINFORCEMENT AS PER  
CODE OR AS SPECIFIED

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER



# NUDURA

INTEGRATED BUILDING TECHNOLOGY

*Building Value.*

NUDURA 6" (152mm) FORM UNIT  
WOOD BUCK MOUNTED  
ALUMINUM TRANSOM AND SIDELIGHT  
AT HEAD AND THRESHOLD  
EXTERIOR FINISH AS SPECIFIED

REV. NO.  
005 KS

REV. DATE:  
SEPT 2010

DRAWN BY:  
T. VAN CLIEAF

DWG NO.  
E6G07

SCALE:  
1 : 8