

NUDURA 6" (152mm)
STANDARD FORM UNIT

1/2" (13mm) GYPSUM
BOARD

EXTERIOR FINISH AS
SPECIFIED

LINTEL REINFORCEMENT
AS PER CODE OR AS
SPECIFIED

VAPOR BARRIER
LAPPED AND SEALED
TO DOOR FRAME

ALUMINUM DRIP CAP
FLASHING INSTALLED BELOW
FINISH FOR FULL FRAME
WIDTH INSTALLED AS PER
CODE OR AS SPECIFIED

EXTENDED DOOR
FRAME SCREWED
DIRECTLY INTO
NUDURA CONCRETE
CORE

OPENING
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

DOOR THRESHOLD

BLOCKING BETWEEN
JOISTS

EXTERIOR CONCRETE
SLAB AND SLOPE AS
PER CODE

FLOOR FINISH
AS SPECIFIED

PROPRIETARY
EMBEDDED JOIST
ANCHORAGE SYSTEM
OR EQUIVALENT

3/16" (5mm) ACRYLIC
PARGE COAT

FLOOR
JOISTS/TRUSSES
AS SPECIFIED

NUDURA 6" (152mm)
TAPER TOP FORM UNIT OR
HAND CUT TAPER BELOW
DOOR OPENING ONLY

LAP VAPOR BARRIER
TO CONTACT DOOR
THRESHOLD

NUDURA WATERPROOFING
MEMBRANE

1/2" (13mm)
GYPSUM BOARD

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 6" (152mm) FORM UNIT
DOOR HEAD/THRESHOLD DETAIL
EXTERIOR FINISH AS SPECIFIED

REV. NO.
000

DWG NO.

DATE:
SEPT 2010

E6G13

DRAWN BY:
K. STILL

SCALE:
1 : 8