

NUDURA 8" (203mm)
STANDARD FORM UNIT

BRICK VENEER c/w
1" (25mm) AIR
SPACE AND BRICK
TIES

WEEP HOLES AND
THROUGH WALL
FLASHING AS PER
CODE OR AS
SPECIFIED

1 1/2"
(38mm) MIN.
COVER

STEEL LINTEL WITH
CONTINUOUS
CAULKING AROUND
FRAME TO MASONRY

BRICK VENEER
BEYOND

ALUMINUM
COMMERCIAL SIDE
LIGHT FRAME

EXTERIOR
CONCRETE
SLAB

NUDURA 8"
(203mm) BRICK
LEDGE FORM
UNIT BEYOND

NUDURA FORM
PANELS c/w INSERT
WEBS—CUT TO SUIT
CONCRETE CAP
PLACEMENT—ADDITIONAL
FORM SUPPORT AS
REQUIRED

1/2" (13mm)
GYPSUM BOARD

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

LINTEL
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

VAPOR BARRIER
SEALED TO CONCRETE

STEEL LINTEL AS
SPECIFIED (w/NELSON
STUDS OR BOLTS AS
PER OPENING
REQUIREMENTS)

FRAME ANCHOR CLIPS
SECURED TO CONCRETE
AND FRAME AS SPECIFIED

OPENING
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

FLOOR FINISH
AS SPECIFIED

CONCRETE
SLAB ON GRADE

COMPRESSIBLE
FELT FILLER STRIP

EPS FOAM CUT DOWN
THICKNESS OF INTERIOR
SLAB AT EXTENT OF
DOOR OPENING WIDTH

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 8" (203mm) FORM UNIT
CONCRETE MOUNTED
ALUMINUM TRANSOM AND SIDE LIGHT
AT HEAD AND CONCRETE THRESHOLD
BRICK VENEER FINISH

REV. NO.
000

REV. DATE:
SEPT 2010

DRAWN BY:
K. STILL

DWG NO.

E8E06

SCALE:

1 : 8