

NUDURA 8" (203mm)
STANDARD FORM UNIT

EXTERIOR FINISH AS
SPECIFIED

MESH BONDED
TO EIFS
LAMINA AT EXTERIOR

FASTEN STUCCO MESH
TO BUCK PRIOR TO
PLACING FRAME
ANCHOR CLIPS

CONTINUOUS AIR SEAL
CAULKING TO FRAME AND
EXTERIOR FINISH

ALUMINUM SIDE LIGHT
FRAME

EXTERIOR CONCRETE
SLAB

COMPRESSIBLE
FELT FILLER
STRIP

NUDURA 8"
(203mm) DOUBLE
TAPER TOP FORM
UNIT OR HAND CUT
TAPER AT WIDTH OF
DOOR OPENING
(BOTH SIDES)

1 1/2"
(38mm) MIN.
COVER

1/2" (13mm)
GYPSUM BOARD

LINTEL
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

VAPOR BARRIER
SEALED TO CONCRETE

WOOD, VINYL, STEEL, ETC.
BUCK MATERIAL FASTENED
TO CONCRETE w/ EMBEDDED
SPIRAL NAILS, BOLTS, SCREWS
IN STAGGERED PATTERN,
OR AS PER
MANUFACTURERS
SPECIFICATIONS

FRAME ANCHOR CLIPS
SECURED TO BUCK AND
FRAME AS SPECIFIED

OPENING
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

FLOOR FINISH
AS SPECIFIED

CONCRETE
SLAB ON GRADE

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 8" (203mm) FORM UNIT
WOOD BUCK MOUNTED
ALUMINUM ENTRANCE DOOR
AT HEAD AND THRESHOLD
EXTERIOR FINISH AS SPECIFIED

REV. NO.
003 KS

REV. DATE:
SEPT 2010

DRAWN BY:
T. VAN CLIEAF

DWG NO.
E8G02

SCALE:
1 : 8