

NUDURA 8" (203mm)
STANDARD FORM UNIT

EXTERIOR FINISH AS
SPECIFIED

MESH BONDED
TO EIFS
LAMINA AT EXTERIOR

FASTEN STUCCO MESH
TO BUCK PRIOR TO
PLACING FRAME
ANCHOR CLIPS

CONTINUOUS AIR SEAL
CAULKING TO FRAME AND
EXTERIOR FINISH

ALUMINUM SIDE LIGHT
FRAME

EXTERIOR CONCRETE
SLAB

NUDURA FORM
PANELS c/w INSERT
WEBS-CUT TO SUIT
CONCRETE CAP
PLACEMENT-ADDITIONAL
FORM SUPPORT AS
REQUIRED

1/2" (13mm)
GYPSUM BOARD

LINTEL
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

VAPOR BARRIER
SEALED TO CONCRETE

WOOD,VINYL,STEEL,ETC.
BUCK MATERIAL FASTENED
TO CONCRETE w/EMBEDDED
SPIRAL NAILS,BOLTS,SCREWS
IN STAGGERED PATTERN,
OR AS PER
MANUFACTURERS
SPECIFICATIONS

FRAME ANCHOR CLIPS
SECURED TO BUCK AND
FRAME AS SPECIFIED

OPENING
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

FLOOR FINISH
AS SPECIFIED

CONCRETE
SLAB ON GRADE

COMPRESSIBLE
FELT FILLER STRIP

EPS FOAM CUT DOWN
THICKNESS OF
INTERIOR SLAB AT
EXTENT OF DOOR
OPENING WIDTH

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

1 1/2"
(38mm) MIN.
COVER

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 8" (203mm) FORM UNIT
WOOD BUCK MOUNTED
ALUMINUM ENTRANCE DOOR
AT HEAD AND CONCRETE THRESHOLD
EXTERIOR FINISH AS SPECIFIED

REV. NO.
000
REV. DATE:
SEPT 2010
DRAWN BY:
K. STILL

DWG NO.
E8G06
SCALE:
1 : 8