

NUDURA 8" (203mm)  
STANDARD FORM UNIT

EXTERIOR FINISH AS  
SPECIFIED

STEEL DOOR

1/2" (13mm) GYPSUM  
BOARD

LINTEL  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

STEEL DOOR FRAME  
c/w CAST IN  
ANCHORS

THRESHOLD

EXTERIOR  
CONCRETE SLAB

COMPRESSIBLE  
FELT FILLER  
STRIP

NUDURA 8" (203mm)  
DOUBLE TAPER TOP  
FORM UNIT OR HAND  
CUT TAPER AT WIDTH OF  
DOOR OPENING (BOTH  
SIDES)

OPENING  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

FLOOR FINISH  
AS SPECIFIED

CONCRETE  
FLOOR SLAB  
ON GRADE

HORIZ/VERT  
REINFORCEMENT  
AS PER CODE  
OR AS SPECIFIED

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER



**NUDURA**

INTEGRATED BUILDING TECHNOLOGY

*Building Value.*

NUDURA 8" (203mm) FORM UNIT  
STEEL DOOR AT HEAD/THRESHOLD  
EXTERIOR FINISH AS SPECIFIED  
DIRECT ATTACHED

REV. NO.  
004 KS

REV. DATE:  
SEPT 2010

DRAWN BY:  
T. VAN CLIEAF

DWG NO.

E8H03

SCALE:  
1 : 8