

NUDURA 8" (203mm)
STANDARD FORM UNIT

EXTERIOR FINISH AS
SPECIFIED

STEEL DOOR

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

LINTEL
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

STEEL DOOR FRAME
c/w CAST IN
ANCHORS

THRESHOLD

EXTERIOR
CONCRETE SLAB

NUDURA FORM
PANELS c/w INSERT
WEBS—CUT TO SUIT
CONCRETE CAP
PLACEMENT—ADDITIONAL
FORM SUPPORT AS
REQUIRED

OPENING
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

FLOOR FINISH
AS SPECIFIED


CONCRETE
FLOOR SLAB
ON GRADE

COMPRESSIBLE
FELT FILLER
STRIP

EPS FOAM CUT DOWN
THICKNESS OF INTERIOR
SLAB AT EXTENT OF
DOOR OPENING WIDTH

HORIZ/VERT
REINFORCEMENT
AS PER CODE
OR AS SPECIFIED

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 8" (203mm) FORM UNIT
STEEL DOOR AT HEAD/THRESHOLD
CONCRETE CAP AT THRESHOLD
EXTERIOR FINISH AS SPECIFIED
DIRECT ATTACHED

REV. NO.
000

REV. DATE:
SEPT 2010

DRAWN BY:
K. STILL

DWG NO.

E8H07

SCALE:

1 : 8