

FLASHING AS SPECIFIED

WOOD BLOCKING AND PLYWOOD AT 5° SLOPE

NON-COMBUSTIBLE FIBERGLASS BATT INSULATION ON VAPOR BARRIER

EPS CANT STRIP

EXTERIOR FINISH AS SPECIFIED

FIBER BOARD SUBSTRATE w/ ROOF MEMBRANE ON 3 1/2" (89mm) RIGID INSULATION

V-CLIP WALL PANEL ANCHOR

FORM PANELS c/w INSERT WEBS-CUT TO SUIT ROOF CONNECTION-ADDITIONAL FORM SUPPORT AS REQUIRED

HOLLOW CORE PRECAST SLAB FINISH AS SPECIFIED

MASONITE BEARING PAD

DOWELS FIELD BENT AND GROUTED INTO SHEAR KEY JOINT BETWEEN PANELS AS SPECIFIED

WET SET DOWELS TO MATCH VERTICAL REINFORCEMENT BETWEEN POUR OR AS SPECIFIED

1/2" (13mm) GYPSUM BOARD

HORIZ/VERT REINFORCEMENT AS PER CODE OR AS SPECIFIED

NUDURA 8" (203mm) STANDARD FORM UNIT

DISCLAIMER NOTICE: SPECIFIC INFORMATION REQUIRED FOR COMPLIANCE WITH LOCAL CODES IS THE RESPONSIBILITY OF THE DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 8" (203mm) FORM UNIT
HOLLOW CORE PRECAST ROOF
EXTERIOR BEARING WALL DETAIL
EXTERIOR FINISH AS SPECIFIED

REV. NO.
003 KS

DWG NO.
F8E01

DATE:
APRIL 2010

DRAWN BY:
T. VAN CLIEAF

SCALE:
1 : 8