

FLASHING AS SPECIFIED

WOOD BLOCKING AND PLYWOOD AT 5° SLOPE

NON-COMBUSTIBLE FIBERGLASS BATT INSULATION ON VAPOR BARRIER

EPS CANT STRIP

FIBER BOARD SUBSTRATE w/ ROOF MEMBRANE ON 3 1/2" (89mm) RIGID INSULATION

BRICK VENEER c/w 1" (25mm) AIR SPACE AND BRICK TIES

FORM PANELS c/w INSERT WEBS-CUT TO SUIT ROOF CONNECTION-ADDITIONAL FORM SUPPORT AS REQUIRED

CAST IN PLACE CONCRETE FLAT SLAB

WET SET DOWELS TO MATCH VERTICAL REINFORCEMENT BETWEEN POUR OR AS SPECIFIED

FINISH AS SPECIFIED

DOWELS FIELD BENT INTO SLAB AS SPECIFIED

HORIZ/VERT REINFORCEMENT AS PER CODE OR AS SPECIFIED

1/2" (13mm) GYPSUM BOARD

NUDURA 8" (203mm) STANDARD FORM UNIT

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER



**NUDURA**

INTEGRATED BUILDING TECHNOLOGY

*Building Value.*

NUDURA 8" (203mm) FORM UNIT  
CONCRETE FLAT PLATE  
EXTERIOR BEARING WALL DETAIL  
BRICK VENEER FINISH

REV. NO. 000	DWG NO. F8G01
DATE: APRIL 2010	
DRAWN BY: K. STILL	SCALE: 1 : 8

DWG NO. F8G01
SCALE: 1 : 8