

NUDURA 10" (254mm)
STANDARD FORM UNIT

ALLOW FLOOR SLAB TO
REST ON TO BEARING WALL
CONCRETE

1/2" (13mm) GYPSUM BOARD

FORM PANELS c/w INSERT
WEBS-CUT TO SUIT FLOOR
CONNECTION-ADDITIONAL FORM
SUPPORT AS REQUIRED

PROPRIETARY STEEL JOIST
FLOOR SYSTEM

PROPRIETARY STEEL JOIST
FLOOR SYSTEM

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

WET SET DOWELS TO MATCH
VERTICAL REINFORCEMENT
BETWEEN POUR OR AS
SPECIFIED

CEILING FINISH AS PER STEEL JOIST
MANUFACTURERS SPECIFICATION
(NOTE: WHERE GYPSUM BOARD IS
REQUIRED TO COMPLETE FIRE RATED
ASSEMBLY, EPS FOAM KERF CUT TO
ENABLE CEILING FINISH TO PROVIDE
THERMAL BARRIER CONTACT TO
CONCRETE)

1/2" (13mm) GYPSUM BOARD

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 10" (254mm) FORM UNIT
PROPRIETARY STEEL JOIST
FLOOR SYSTEM
NON-BEARING DEMISING WALL DETAIL

REV. NO.
000

DATE:
APRIL 2010

DRAWN BY:
K. STILL

DWG NO.

G10B02

SCALE:

1 : 8