



NUDURA 12" (305mm)  
STANDARD FORM UNIT

HORIZ/VERT  
REINFORCEMENT AS PER  
CODE OR AS SPECIFIED

COMPOSITE STEEL DECK  
WELDED TO SUPPORT  
ANCHORS AS SPECIFIED

WET SET DOWELS FIELD  
BENT INTO SLAB AS  
SPECIFIED

WET SET DOWELS TO  
MATCH VERTICAL  
REINFORCEMENT  
BETWEEN POUR OR AS  
SPECIFIED

1/2" (13mm) GYPSUM  
BOARD

FORM PANELS c/w  
INSERT WEBS-CUT TO  
SUIT FLOOR  
CONNECTION-ADDITIONAL  
FORM SUPPORT AS  
REQUIRED

COMPOSITE STEEL  
DECK-SLAB AND  
REINFORCEMENT AS  
SPECIFIED

INTERIOR INSULATION  
TO BE DISCONTINUOUS  
AT FLOOR LINES

OWSJ

MIN. 1/32" (0.8mm) x 2 1/2"  
(63.5mm) GALVANIZED  
STEEL CHANNEL CAP TO  
PROVIDE THERMAL BARRIER  
PROTECTION

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER



NUDURA 12" (305mm) FORM UNIT COMPOSITE STEEL DECK-SLAB STEEL JOISTS ON NON-BEARING DEMISING WALL	
REV. NO. 000	DWG NO. G12C02
DATE: APRIL 2010	
DRAWN BY: K. STILL	SCALE: 1 : 8