

NUDURA 6"
(152mm)
STANDARD FORM
UNIT

BRICK VENEER
c/w 1" (25mm)
AIR SPACE AND
BRICK TIES

THROUGH WALL
FLASHING AS
PER CODE OR
AS SPECIFIED

1 1/2"
(38mm) MIN.
COVER

STEEL LINTEL

FOAM BACKER
ROD AND
CONTINUOUS
CAULKING
AROUND FRAME
TO MASONRY

WINDOW FRAMING
BY OTHERS

1/2" (13mm)
GYPSUM BOARD

HORIZ/VERT
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

LINTEL
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

WOOD, VINYL, STEEL,
ETC. BUCK MATERIAL
FASTENING TO CONCRETE
w/ EMBEDDED SPIRAL
NAILS, BOLTS, SCREWS
IN STAGGERED PATTERN,
OR AS PER
MANUFACTURERS
SPECIFICATION

GYPSUM BOARD
RETURN TO FRAME

VAPOR BARRIER
c/w FOAM
ROD/CAULK TO
SEAL TO INTERIOR
EDGE OF FRAME

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER

THIS DETAIL IS SUITABLE FOR
NON-COMBUSTIBLE 1 TO 3 STOREY HIGH
APPLICATIONS AS PERMITTED UNDER LOCAL
CODES; FOR WINDOWS IN BRICK CLAD
MULTI-STOREY APPLICATIONS, REFER TO DETAIL
H6A04 & H6A05 UNDER THIS SECTION



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 6" (152mm) FORM UNIT
WINDOW HEAD DETAIL
BRICK VENEER FINISH
ALUMINUM FRAMED WINDOW
WOOD ROUGH BUCK

REV. NO.
000

DATE:
JUNE 2010

DRAWN BY:
K. STILL

DWG NO.

H6A01

SCALE:

1 : 4