

NUDURA 6"
(152mm)
STANDARD FORM
UNIT

BRICK VENEER
c/w 1" (25mm)
AIR SPACE AND
BRICK TIES

THROUGH WALL
FLASHING AS
PER CODE OR
AS SPECIFIED

FIRE CAULK APPLIED
TO BACKSIDE OF
STEEL LINTEL BEFORE
INSTALLATION

STEEL LINTEL

FOAM BACKER
ROD AND
CONTINUOUS
CAULKING
AROUND FRAME
TO MASONRY

WINDOW FRAMING
BY OTHERS

1/2" (13mm)
GYPSUM BOARD

HORIZ/VERT
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

LINTEL
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

1 1/2"
(38mm) MIN.
COVER

GYPSUM BOARD
RETURN TO FRAME

VAPOR BARRIER
c/w FOAM
ROD/CAULK TO
SEAL TO INTERIOR
EDGE OF FRAME

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 6" (152mm) FORM UNIT
WINDOW HEAD DETAIL
BRICK VENEER FINISH
FOR LOOSE FIT STEEL LINTEL
COMPLIANT OPENINGS

REV. NO.
001 KS

DATE:
MARCH 2013

DRAWN BY:
K. STILL

DWG NO.

H6A04a

SCALE:

1 : 4