

NUDURA 6" (152mm)
STANDARD FORM UNIT

VERTICAL METAL SIDING AS
SPECIFIED

THROUGH WALL FLASHING
AS PER CODE OR AS
SPECIFIED

FOAM BACKER ROD
AND CONTINUOUS
CAULKING AROUND
FRAME

WINDOW FRAMING
BY OTHERS

1/2" (13mm)
GYPSUM BOARD

HORIZ/VERT
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

LINTEL
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

1 1/2"
(38mm) MIN.
COVER

GYPSUM BOARD
RETURN TO FRAME

VAPOR BARRIER
c/w FOAM
ROD/CAULK TO
SEAL TO INTERIOR
EDGE OF FRAME

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 6" (152mm) FORM UNIT
WINDOW HEAD DETAIL
VERTICAL SIDING FINISH
ALUMINUM FRAMED WINDOW
CONCRETE MOUNTED

REV. NO.
000

DATE:
JUNE 2010

DRAWN BY:
K. STILL

DWG. NO.

H6B04

SCALE:

1 : 4