

NUDURA 6"
(152mm)
STANDARD FORM
UNIT

WOOD SIDING NAILED
TO STRAPPING AS
SPECIFIED

1"x2" (25mm x 51mm)
WOOD STRAPPING
SCREWED TO FASTENING
STRIPS AS SPECIFIED

THROUGH WALL
FLASHING AS PER
CODE OR AS
SPECIFIED

1 1/2"
(38mm) MIN.
COVER

WINDOW FRAMING
BY OTHERS

1/2" (13mm)
GYPSUM BOARD

HORIZ/VERT
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

LINTEL
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

WOOD, VINYL, STEEL, ETC.
BUCK MATERIAL
FASTENING TO CONCRETE
w/ EMBEDDED SPIRAL
NAILS, BOLTS, SCREWS IN
STAGGERED PATTERN, OR
AS PER MANUFACTURERS
SPECIFICATION

GYPSUM BOARD
RETURN TO FRAME

VAPOR BARRIER
SEALED TO
INTERIOR EDGE OF
FRAME

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 6" (152mm) FORM UNIT
WINDOW HEAD DETAIL
HORIZONTAL WOOD SIDING FINISH
ALUMINUM FRAMED WINDOW
WOOD ROUGH BUCK

REV. NO.
000

DATE:
AUGUST 2010

DRAWN BY:
K. STILL

DWG NO.

H6B07

SCALE:

1 : 4