

NUDURA 6" (152mm)
STANDARD FORM UNIT

DIRECT APPLIED
ACRYLIC FINISH

FASTEN STUCCO MESH
TO BUCK PRIOR TO
PLACING BUCK AT
HEAD CONDITION

FOR MULTI-STOREY
APPLICATIONS, EIFS
LAMINA TO LAP BACK
AROUND BUCK TO
LINK w/ CONCRETE

1 1/2"
(38mm) MIN.
COVER

FOAM BACKER ROD
AND CONTINUOUS
CAULKING AROUND
FRAME

WINDOW FRAMING BY
OTHERS

1/2" (13mm)
GYPSUM BOARD

HORIZ/VERT
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

LINTEL
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

WOOD, VINYL, STEEL,
ETC. BUCK MATERIAL
FASTENING TO CONCRETE
w/ EMBEDDED SPIRAL
NAILS, BOLTS, SCREW IN
STAGGERED PATTERN, OR
AS PER MANUFACTURERS
SPECIFICATION

GYPSUM BOARD RETURN
TO FRAME

VAPOR BARRIER c/w
FOAM ROD/CAULK
TO SEAL TO
INTERIOR EDGE OF
FRAME

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 6" (152mm) FORM UNIT
WINDOW HEAD DETAIL
DIRECT APPLIED ACRYLIC FINISH
ALUMINUM FRAMED WINDOW
WOOD ROUGH BUCK

REV. NO.
000

REV. DATE:
JUNE 2010

DRAWN BY:
K. STILL

DWG NO.

H6C01

SCALE:

1 : 4