

WINDOW FRAMING  
BY OTHERS

FOR MULTI-STOREY  
APPLICATIONS, EIFS  
LAMINA TO LAP  
BACK AROUND  
BUCK TO LINK w/  
CONCRETE

FOAM BACKER ROD  
AND CONTINUOUS  
CAULKING AROUND  
FRAME

OPENING  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

NUDURA 6" (152mm)  
STANDARD FORM UNIT

DIRECT APPLIED  
ACRYLIC FINISH

GYPSUM BOARD RETURN  
TO FRAME

VAPOR BARRIER SEALED  
TO FRAME AT SILL  
CONDITION

COMPRESSIBLE AIR SEAL  
GASKET APPLIED TO  
FULL LENGTH REAR  
EDGE OF SILL PRIOR TO  
FRAME INSTALLATION

HORIZ/VERT  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

$\frac{1}{2}$ " (13mm)  
GYPSUM BOARD

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER



# NUDURA

INTEGRATED BUILDING TECHNOLOGY

*Building Value.*

NUDURA 6" (152mm) FORM UNIT  
WINDOW SILL DETAIL  
DIRECT APPLIED ACRYLIC FINISH  
ALUMINUM FRAMED WINDOW  
CONCRETE MOUNTED

REV. NO.  
000

REV. DATE:  
JUNE 2010

DRAWN BY:  
K. STILL

DWG NO.

H6C05

SCALE:

1 : 4